

Development of Hopfield Artificial Neural Network for Anomaly Detection in Environmental Gamma Radiation Background

Consortium on Nuclear Security Technologies (CONNECT) Q2 Report

Nuclear Science and Engineering Division

About Argonne National Laboratory

Argonne is a U.S. Department of Energy laboratory managed by UChicago Argonne, LLC under contract DE-AC02-06CH11357. The Laboratory's main facility is outside Chicago, at 9700 South Cass Avenue, Argonne, Illinois 60439. For information about Argonne and its pioneering science and technology programs, see www.anl.gov.

Document availability

Online Access: U.S. Department of Energy (DOE) reports produced after 1991 and a growing number of pre-1991 documents are available free at OSTI.GOV (<http://www.osti.gov/>), a service of the U.S. Dept. of Energy's Office of Scientific and Technical Information

Reports not in digital format may be purchased by the public from the National Technical Information Service (NTIS):

U.S. Department of Commerce
National Technical Information Service
5301 Shawnee Rd
Alexandria, VA 22312
www.ntis.gov
Phone: (800) 553-NTIS (6847) or (703) 605-6000
Fax: (703) 605-6900
Email: **orders@ntis.gov**

Reports not in digital format are available to DOE and DOE contractors from the Office of Scientific and Technical Information (OSTI):

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062
www.osti.gov
Phone: (865) 576-8401
Fax: (865) 576-5728
Email: **reports@osti.gov**

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor UChicago Argonne, LLC, nor any of their employees or officers, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of document authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof, Argonne National Laboratory, or UChicago Argonne, LLC.

Development of Hopfield Artificial Neural Network for Anomaly Detection in Environmental Gamma Radiation Background

Consortium on Nuclear Security Technologies (CONNECT) Q2 Report

prepared by
Luis Valdez^{1,2}, Alexander Heifetz¹

¹Nuclear Science Engineering Division, Argonne National Laboratory

²Department of Electrical and Computer Engineering, University of Texas at San Antonio

April 30, 2021

Table of Contents

Table of Contents	1
List of Figures	2
Abstract	3
1. Introduction	4
2. Hopfield Artificial Neural Networks for Anomaly Detection	5
2.1. Hopfield Artificial Neural Network (HANN) Description	5
2.2. Image Processing Algorithm for Gamma Spectroscopy in Search Survey	6
3. Conclusions	7
References	8

List of Figures

Figure 1 – Gamma counts, measured while driving with NaI detector through sections of the city of Chicago, displayed with pseudo color. Brighter colors indicate larger number of total counts.	4
Figure 2 – Hopfield Artificial Neural Network structure	6
Figure 3 – Grayscale image of gamma counts per second (CPS).....	6

Abstract

Environmental screening of gamma radiation consists of detecting weak nuisance and anomaly signal in the presence of strong and highly varying background. In a typical scenario, a mobile detector-spectrometer continuously measures gamma radiation spectra in short, e.g., one-second, signal acquisition intervals. The measurement data is a 2D matrix, where one dimension is gamma ray energy, and the other dimension is the number of measurements or total time. In principle, gamma radiation sources can be detected and identified from the measured data by their unique spectral lines. Detecting sources from data measured in a search scenario is difficult due to the highly varying background because of naturally occurring radioactive material (NORM), and low signal-to-noise ratio (S/N) of spectral signal measured during one-second acquisition intervals. The objective of this work is to explore *supervised* machine learning (ML) algorithms for development of a Hopfield Neural Network (HNN) in conjunction with an image processing algorithm for detection and identification of weak nuisances and anomalies events in the presence of a highly fluctuating background.

1. Introduction

Environmental screening of gamma radiation consists of detecting weak nuisance and anomaly signal in the presence of strong and highly varying background. In a typical scenario, a mobile detector-spectrometer continuously measures gamma radiation spectra in short, e.g., one-second, signal acquisition intervals. The measurement data is a 2D matrix, where one dimension is gamma ray energy, and the other dimension is the number of measurements or total time. In principle, gamma radiation sources can be detected and identified from the measured data by their unique spectral lines. Detecting sources from data measured in a search scenario is difficult due to the highly varying background because of naturally occurring radioactive material (NORM), and low signal-to-noise ratio (S/N) of spectral signal measured during one-second acquisition intervals. The objective of this work is to explore *supervised* machine learning (ML) algorithms for detection and identification of weak nuisances and anomalies events in the presence of highly fluctuating background. As an example, Figure 1 shows images of gamma counts obtained with NaI detectors placed on a mobile platform in a drive through portions of the city of Chicago. Gamma counts per second (CPS), which are integrated over the energy spectrum, are displayed on the city map with pseudo color. Brighter counts indicate larger number of total counts. As seen in the figure, there is significant fluctuation of gamma counts due to NORM in an urban setting.




Figure 1 – Gamma counts, measured while driving with NaI detector through sections of the city of Chicago, displayed with pseudo color. Brighter colors indicate larger number of total counts.

In this work, we develop a Hopfield Artificial Neural Networks (HANN) in conjunction with an image processing algorithm to detect a weak signal anomaly hidden among the highly fluctuating background spectra. HANN is an associative memory algorithm inspired by the ability of a human brain to recognize objects from memory of past observations. The anomaly is the unstable orphan isotope that appears in the natural background consisting from gamma radiation by primordial isotopes. As part of HNN data analysis, the measurement 2D matrix is converted into an image, where the intensity of each pixel is given by counts per second (CPS).

2. Hopfield Artificial Neural Networks for Anomaly Detection

2.1. Hopfield Artificial Neural Network (HANN) Description

HANN is an associative memory algorithm inspired by human brain ability to learn from observations. The brain consists of neurons transmitting signals through the nervous system. The transmitting part of neurons are axons, which are long thin structures in which action potentials are generated. The receiving part of a neuron is a dendrite, which receives synaptic inputs from axons. The total sum of dendritic inputs determines if the neuron will fire an action potential [4]. HANN is a recurrent artificial neural network and a type of spin glass or Ising model, which provides model for understanding human memory [4]. HANN contains artificial neurons, which are binary threshold units, with the values of the states depending on unit's input exceeding its threshold. The interactions between neurons take values of 1 or -1 synaptic weights. Information is delivered to the next neuron that can be an output neuron or a process neuron. HANN implements an auto-associative memory by interconnecting each artificial neuron with all others, but not with themselves. The interactions of HANN neuron's are learned through Hebbian law of association [4], which provides a method to model memory for image reconstruction and pattern recognition. The weight matrix W matrix, calculated in Equation (1), is the sum of each independent weight of each neuron. Here x represents the training mode of the input vector.

$$W = \sum_i^N x_i * x_i^T \quad (1)$$

Discrete HNN has two ways to update and retrieve a memory pattern. The first one is asynchronous, which consists of updating one neuron at time until the system converges to a desired output. This is a very efficient method when the memory storage requires several samples to be memorized, but slows down the processing time of the system. The second one is synchronous, in which all neurons fire at once. Updating the system, we repeat the process several times until system converges to the desired output. Equation 2 describes these processes, where Y is the output, x is the input, and ξ represents a distorted input.

$$Y = \text{sgn}(W * \xi^T) \quad (2)$$

The weight matrix contains the memory patterns, which is used to retrieve the desired data by inputting the test data and iterate the neural network from state to state until it retrieves the correct pattern. This response is accomplished by the feedback characteristic of the system that allows the output to correct itself by iteration through the system until convergence. The diagram of a HANN is depicted in Figure 1.




Figure 2 – Hopfield Artificial Neural Network structure

2.2. Image Processing Algorithm for Gamma Spectroscopy in Search Survey

Interactions between HANN neurons have units that take on values $[1, -1]$. To use HANN on a data set requires conversion of data to binary threshold HANN units. This is accomplished by converting original data into a grayscale intensity image, thresholding and normalizing the data to the set of binary values $[1, 0]$, and then converting the zero values to -1 's. This process is illustrated in Figures 3 and 4. An example of grayscale intensity image of counts per second (CPS) for various energies and times is shown in Figure 3. The data set consists of 5827 one-second measurements of gamma spectra with NaI(Tl) detector-spectrometer with 1024 spectral channels and energy bandwidth from 0 to 3000keV. Grayscale intensity image of CPS is plotted with MATLAB.




Figure 3 – Grayscale image of gamma counts per second (CPS)

3. Conclusions

We have investigated a Hopfield Artificial Neural Networks (HANN) together with an image processing algorithm to detect a weak signal anomaly hidden among the highly fluctuating background spectra. HANN is an associative memory algorithm inspired by the ability of a human brain to recognize objects from memory of past observations. The anomaly is the unstable orphan isotope that appears in the natural background consisting from gamma radiation by primordial isotopes. As part of HNN data analysis, the measurement 2D matrix is converted into an image, where the intensity of each pixel is given by counts per second (CPS).

References

1. Weinstein, M., Heifetz, A., & Klann, R. (2014). Detection of nuclear sources in search survey using dynamic quantum clustering of gamma-ray spectral data. *The European Physical Journal Plus*, 129(11), 239.
2. Alamaniotis, M., Heifetz, A., Raptis, A. C., & Tsoukalas, L. H. (2013). Fuzzy-logic radioisotope identifier for gamma spectroscopy in source search. *IEEE Transactions on Nuclear Science*, 60(4), 3014-3024.
3. Bai, E. W., Heifetz, A., Raptis, P., Dasgupta, S., & Mudumbai, R. (2015). Maximum likelihood localization of radioactive sources against a highly fluctuating background. *IEEE Transactions on Nuclear Science*, 62(6), 3274-3282.
4. Hopfield J.J. (1982). Neural networks and physical systems with emergent collective computational abilities. *Proceedings of the National Academy of Sciences of the United States of America*, 79(8), 2554–2558.



Nuclear Science and Engineering (NSE) Division

Argonne National Laboratory

9700 South Cass Avenue, Bldg. 208

Argonne, IL 60439

www.anl.gov



Argonne National Laboratory is a U.S. Department of Energy
laboratory managed by UChicago Argonne, LLC